



## NC110XA Security Camera

Massive 107° field of view. Built-in PIR sensor to trigger recording from moving heat. Reduces false alarms and increases storage time.

5  
MEGA  
PIXELS

2.8mm  
LENS

PIR

### Specifications

|                                       |                                                                                                              |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Camera Type                           | Dome                                                                                                         |
| Image Sensor                          | 1/2.7" Progressive CMOS                                                                                      |
| Maximum Video Resolution (Megapixels) | 5                                                                                                            |
| Maximum Video Resolution              | 2592 x 1944                                                                                                  |
| Lens                                  | 2.8 mm (H.FOV: 107°)                                                                                         |
| Lens Type                             | Fixed                                                                                                        |
| Maximum Night IR Distance (M)         | 30                                                                                                           |
| Image clarity                         | 3                                                                                                            |
| Connectors                            | RJ-45                                                                                                        |
| Video Compression                     | H.265, H.264                                                                                                 |
| ONVIF (depends on firmware version)   | 2.6                                                                                                          |
| Operating Environment                 | -10°C to 55°C (14°F-131°F) Humidity: 20%-80% RH                                                              |
| Dimensions                            | 100×100 mm                                                                                                   |
| Weight (Net)                          | 0.4                                                                                                          |
| Accessories                           | IV2422X, IV2433X, IV2444X, IV2455X                                                                           |
| Power Supply                          | Power over Ethernet IEEE 802.3af, DC12V                                                                      |
| Power Consumption                     | <7W                                                                                                          |
| Connectors (web)                      | RJ-45 , DC Power Input                                                                                       |
| Outdoor Use                           | Yes                                                                                                          |
| IP Rating                             | IP66                                                                                                         |
| Vandal Resistant                      | Yes                                                                                                          |
| Frame Rate at Resolution              | 15                                                                                                           |
| Day/Night Mode                        | Auto                                                                                                         |
| Image Enhancement                     | Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue                                                  |
| Video Compression                     | H.265, H.264 (2 streams)                                                                                     |
| Protocols                             | TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPoE, UPNP, SMTP, SNMP, P2P (QR code)        |
| Software                              | Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app                                         |
| Power Over Ethernet                   | Yes                                                                                                          |
| Ethernet                              | Ethernet (10/100 Base-T)                                                                                     |
| UPNP                                  | Yes                                                                                                          |
| In The Box                            | Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs |
| Warranty                              | 3 Year Warranty                                                                                              |
| Weight (Packaged)                     | 0.55                                                                                                         |